



**SDB-LED MEDIUM INTENSITY**  
**TYPE L-865/ L-864**

**SPECIFICATION**

|  |  |
|--|--|
| <b>Intensity</b>                       | <b>Medium</b>  |
| <b>Horizontal Coverage</b>             | <b>360°</b>  |
| <b>Vertical Beam</b>                   | <b>3° Minimum</b>  |
| <b>Lens Material</b>                   | <b>Hard Glass</b>  |
| <b>Effective Candelas (Day Mode)</b>   | <b>20,000 Nominal</b>  |
| <b>Effective Candelas (Night Mode)</b> | <b>2,000 Nominal</b>   |
| <b>Effective Candelas (Fail Mode)</b>  | <b>2,000 Nominal</b>   |
| <b>Flashes Per Minute (Day Mode)</b>   | <b>40 per minute</b>   |
| <b>Flashes Per Minute (Night Mode)</b> | <b>40 per minute</b>   |
| <b>Flashes Per Minute (Fail Mode)</b>  | <b>40 per minute</b>   |
| <b>Height</b>                          | <b>10"</b>   |
| <b>Diameter</b>                        | <b>20"</b>   |
| <b>Flashhead Base Material</b>         | <b>Powder Coated Stainless Steel (White)</b>                 |
| <b>Voltage</b>                         | <b>110VAC-240Vac -50/60 HZ (Available in other voltages)</b> |
| <b>Wattage (Day Mode)</b>              | <b>75 Watts</b>  |
| <b>Wattage (Night Mode)</b>            | <b>15 Watts</b>  |
| <b>Wattage (Fail Mode)</b>             | <b>25 Watts</b>  |
| <b>Weight (Flashhead)</b>              | <b>30 lbs</b>  |
| <b>Operating Temperature</b>           | <b>-55 C° to +55 C°</b>                                      |
| <b>Wind Load</b>                       | <b>CAAA= 1.7 FT2</b>   |
| <b>Mounting Holes</b>                  | <b>Six mounting holes 17.5mm on a 14.6" bolt circle</b>      |
| <b>Hardware Material</b>               | <b>Stainless Steel</b>                                       |

**QUALITY:**

- RESISTANT TO HEAVY RAIN OR STORMS AND CORROSION.
- RESISTANT TO SHOCK AND VIBRATION.
- HARD GLASS PROJECTORS COVER PREVENTING UV RADIATION AGING AND LOSS OF LIGHT INTENSITY.

**ADVANTAGES:**

- ETL CERTIFIED TO FAA (AC-150/5345-43G & EB67D).
- MODULAR DESIGN.
- EASE OF MAINTENANCE BY THE USE OF 6 INDEPENDENT PROJECTORS.
- GPS AND FIBER OPTICS SYNCHRONIZATION AVAILABLE.
- MASTER/SLAVE CONFIGURATION FOR MULTIPLE LIGHTS SITES.
- ONLINE REAL TIME DIAGNOSTIC AVAILABLE TO END-USER FOR PREVENTIVE MAINTENANCE AS WELL.
- ALARM CONTACT AVAILABLE
- LOW POWER CONSUMPTION
- APPLICATIONS: TOWERS, CHIMNEYS, BRIDGES, BUILDINGS AND OTHER STRUCTURES.
- PRICE INCLUDES: COMPLETE FLASHHEAD, CONTROLLER CABINETS AND POWER SUPPLY.

**IMPORTANT:**

- THIS FIXTURE IS DESIGNED TO BE USED WITH ITS CONTROLLER.
- TECHNICAL SERVICE AVAILABLE 24/365.
- THE USE OF NON-OEM PARTS WILL VOID WARRANTY.

**Siccteco USA & Lighting, 10939 Timber Oak Dr. Houston TX 77043**  
**Ph: 713 - 467 - 4778, Cell: 713-382-9906, Fax: 713 - 467 - 4777**  
**WWW.SICTTECOLIGHTING.COM**

