



S-2LED DOUBLE RED LED LIGHT
TYPE L-810
SPECIFICATIONS

INTENSITY LEVEL:	LOW
HORIZONTAL COVERAGE:	360°
VERTICAL LIGHT EXPANSION:	MINIMUM 10°
LAMP DESCRIPTION:	LED
EFFECTIVE CANDELA:	65 MINIMUM
LAMP HEIGHT:	7.5" TALL
LAMP DIAMETER:	4.875"
LAMP LENGTH:	11.5"
LAMP BASE MATERIAL:	ALUMINUM A-356, OVEN-BAKED PAINTED (WHITE)
LENS MATERIAL:	PYREX GLASS
POWER OR VOLTAGE REQUIREMENT:	90 VAC / 260 VAC 60 HZ
AVAILABLE IN OTHER VOLTAGES:	12 / 24 / 48 VDC
WATTAGE:	4.8 WATTS
WEIGHT:	7 lbs.
OPERATING TEMPERATURE:	-55°C TO +55°C
WIND LOAD:	CAAA = 0.4 FT ²
HOLE SIZE:	0.75", 1" OR 1.25" NPT (BOTTOM HOLE)
LATCHES, SAFETY CABLE, AND SCREWS:	STAINLESS STEEL

ADVANTAGES:

- LOW ENERGY CONSUMPTION UP TO 95% LESS COMPARED TO INCANDESCENT DOUBLE LIGHTS.
- THIS LIGHT COMPLIES WITH THE REQUIREMENTS DEMANDED BY THE FAA / DGAC / ICAO.
- MANUFACTURE WARRANTY FOR LIGHT IS 5 YEARS.
- DESIGNED TO DIRECTLY REPLACE EXISTING INCANDESCENT DOUBLE LIGHTS ON ANY TOWER OR BUILDINGS USING THE SAME WIRING.
- OUR LIGHTS CAN OPERATE UNDER ANY SEASON: STORMY WINTERS, TEMPORARY CLOUDY DAYS, AS WELL AS MILD SUMMERS.

QUALITY:

- THIS PRODUCT IS OF HIGH QUALITY AND IT DOES NOT REQUIRE PREVENTIVE MAINTENANCE AFTER APPROPRIATE INSTALLATION.
- RESISTANT TO CORROSION, STRONG STORMS, VIBRATIONS, AND MODERATE IMPACTS; DUE TO THE QUALITY OF ITS MATERIAL.

NOTE:

- LIGHT DESIGNED TO FLASH OR OPERATE IN STEADY MODE WITH THE FOLLOWING CONTROLLERS:
 - **SC-0MLED** (ALARMED CONTROL) FOR (1) **S-2LED** LIGHT ABOVE (3) STEADY **S-1LED** LIGHTS IN THE MIDDLE OF THE TOWER OR (9) **S-1LED** LIGHTS.
 - **SC-OWFLED** (UNALARMED CONTROL) FOR (1) FLASHING **S-2LED** LIGHT (3) STEADY **S-1LED** LIGHTS IN THE MIDDLE OF THE TOWER OR (9) **S-1LED** LIGHTS.
 - **SC-OLED** (UNALARMED CONTROL) FOR (1) **S-2LED** LIGHT (3) STEADY **S-1LED** LIGHTS IN THE MIDDLE OF THE TOWER OR (9) **S-1LED** LIGHTS.
- WARRANTY FOR THE CONTROLLERS: 2 YEARS AND 5 YEARS FOR THE LED LIGHT AFTER PROPER INSTALLATION.
- PRODUCT AND SPARE PARTS (REPLACEMENTS) ARE AVAILABLE FOR IMMEDIATE SHIPPING.
- TECHNICAL SUPPORT 24HRS, 365 DAYS A YEAR.

OBSERVATION:

Sictec Lighting Corp. 10939 Timber Oak Dr. Houston TX 77043
Ph: 713 - 467 - 4778, Cell: 713-382-9906
WWW.SICTTECOLIGHTING.COM

