



S-1 SINGLE INCANDESCENT RED LIGHT

TYPE L-810
SPECIFICATIONS

INTENSITY LEVEL:	LOW
HORIZONTAL COVERAGE:	360°
VERTICAL LIGHT EXPANSION:	MINIMUM 10°
WEIGHT:	3 LBS.
BULB:	(1) 116 WATTS 120VAC
EFFECTIVE CANDELA:	32.5 MINIMUM
LAMP HEIGHT:	7.5" TALL
LAMP DIAMETER	4.875"
LAMP BASE MATERIAL:	ALUMINUM A-356
LENS MATERIAL:	FRESNEL PYREX GLASS
POWER OR VOLTAGE REQUIREMENT:	120 VAC, 60HZ (AVAILABLE IN OTHER VOLTAGES)
WATTAGE:	116 WATTS
OPERATING TEMPERATURE:	-55°C TO +55°C.
WIND LOAD:	CAAA= 0.2 SQ. FT.
HOLE SIZES:	0.75", 1", OR 1.25" NPT (SIDE AND BOTTOM HOLES)
CLIPS, SAFETY CABLE, AND SCREWS	STAINLESS STEEL
BULB HOLDER MATERIAL:	CERAMIC

ADVANTAGES:

- THIS LIGHT MEETS THE REQUIREMENTS DEMANDED BY THE **FAA / DGAC / ICAO**.
- DESIGNED TO BE INSTALLED ON TOWERS, BUILDINGS, OR OTHER STRUCTURES THAT REQUIRE THIS TYPE OF SIGNAL.
- BASE AND RING ARE ALUMINUM A-356.
- THIS LIGHT HAS TWO HOLES (SIDE AND BOTTOM), ALLOWING EASY INSTALLATION, OFFERING THE CUSTOMER THE OPPORTUNITY TO CHOOSE WHICH HOLE TO USE IN A SINGLE LAMP WITHOUT IT UNDERGOING ANY TYPE OF SUBSEQUENT MODIFICATION OR ALTERATION.
- OUR LIGHTS CAN OPERATE UNDER ANY SEASON: STORMY WINTERS, PARTLY CLOUDY DAYS, AS WELL AS MILD SUMMERS.

QUALITY:

- RESISTANT TO CORROSION, STRONG STORMS, VIBRATIONS, AND MODERATE IMPACTS DUE TO THE QUALITY OF ITS MATERIAL.

NOTE:

- LIGHT DESIGNED TO FLASH OR OPERATE IN STEADY MODE WITH THE FOLLOWING CONTROLLERS:
 - **SC-0M** (ALARMED CONTROL) FOR (1) S-2 LIGHT ABOVE (3) STEADY S-1 LIGHTS IN THE MIDDLE OF THE TOWER OR (9) S-1 LIGHTS.
 - **SC-OWF** (UNALARMED CONTROL) FOR (1) S-2 LIGHT ABOVE FLASHING (3) STEADY S-1 LIGHTS IN THE MIDDLE OF THE TOWER OR (9) S-1 LIGHTS.
 - **SC-O** (UNALARMED CONTROL) FOR (1) S-2 LIGHT ABOVE (3) STEADY S-1 LIGHTS IN THE MIDDLE OF THE TOWER OR (9) S-1 LIGHTS.
- WARRANTY FOR CONTROLLERS AND LIGHT: 2 YEARS AFTER THEIR OWN INSTALLATION (LIGHT BULBS ARE NOT INCLUDED IN SUCH WARRANTY).
- PRODUCT AND REPLACEMENT PARTS ARE AVAILABLE FOR IMMEDIATE SHIPPING.
- TECHNICAL SUPPORT 24HRS, 365 DAYS A YEAR.

Sictec Lighting Corp. 10939 Timber Oak Dr. Houston TX 77043
Ph: 713 - 467 - 4778, Cell: 713-382-9906
WWW.SICTTECOLIGHTING.COM

