



S-2 DOUBLE INCANDESCENT RED LIGHT
TYPE L-810
SPECIFICATIONS

INTENSITY LEVEL:	LOW
HORIZONTAL COVERAGE:	360°
VERTICAL LIGHT EXPANSION:	MINIMUM 10°
BULBS:	(2) OF 116 WATTS EACH 120VAC
EFFECTIVE CANDELA:	65 MINIMUM
LAMP HEIGHT:	7.5" TALL
LAMP DIAMETER:	4.875"
LAMP LENGTH:	11.5"
LAMP MATERIAL:	ALUMINUM A-356
LENS MATERIAL:	FRESNEL PYREX GLASS
POWER OR VOLTAGE REQUIREMENT:	120 VAC, 60 HZ (AVAILABLE IN OTHER VOLTAGES)
WATTAGE:	232 WATTS
WEIGHT:	7 LBS.
OPERATING TEMPERATURE:	-55°C to +55°C.
WIND LOAD:	CAA=0.5 FT ²
HOLE SIZE:	0.75", 1" OR 1.25" NPT (BOTTOM HOLE)
LATCHES, SAFETY CABLE, AND SCREWS:	STAINLESS STEEL
BULB HOLDERS MATERIAL:	CERAMIC

ADVANTAGES:

- THIS LIGHT MEETS THE REQUIREMENTS DEMANDED BY THE FAA / DGAC / ICAO.
- DESIGNED TO BE INSTALLED ON TOWERS, BUILDINGS, OR OTHER STRUCTURES REQUIRING THIS TYPE OF SIGNAL.
- BASE AND RINGS ALUMINUM.
- OUR LIGHTS CAN OPERATE UNDER ANY SEASON: STORMY WINTERS, PARTLY CLOUDY DAYS, AS WELL AS MILD SUMMERS.

QUALITY:

- RESISTANT TO CORROSION, STRONG STORMS, VIBRATIONS, AND MODERATE IMPACTS DUE TO THE QUALITY OF ITS MATERIAL.

NOTE:

- LIGHT DESIGNED TO FLASH OR OPERATE IN STEADY MODE WITH THE FOLLOWING CONTROLLERS:
 - SC-0M (ALARMED CONTROL) FOR (1) S-2 LIGHT ABOVE AND (3) STEADY S-1 LIGHTS IN THE MIDDLE OF THE TOWER OR (9) S-1 LIGHTS.
 - SC-OWF (UNALARMED CONTROL) FOR (1) S-2 LIGHT ABOVE FLASHING (3) STEADY S-1 LIGHTS IN THE MIDDLE OF THE TOWER OR (9) S-1 LIGHTS.
 - SC-O (UNALARMED CONTROL) FOR (1) S-2 LIGHT ABOVE AND (3) STEADY S-1 LIGHTS IN THE MIDDLE OF THE TOWER OR (9) S-1 LIGHTS.
- WARRANTY FOR CONTROLLERS AND LIGHT: 2 YEARS AFTER ITS PROPER INSTALLATION (LIGHT BULBS ARE NOT INCLUDED IN THIS WARRANTY).
- PRODUCTS AND SPARE PARTS ARE AVAILABLE FOR IMMEDIATE SHIPPING.
- TECHNICAL SUPPORT, 24 HOURS A DAY, 365 DAYS A YEAR.

Sictteco Lighting Corp. 10939 Timber Oak Dr. Houston TX 77043
Ph: 713 - 467 - 4778, Cell: 713-382-9906
WWW.SICTTECOLIGHTING.COM

