



**SICTTECO LED STREET LIGHT
TYPE SSL-1-100W
SPECIFICATIONS**

MODEL	SSL-1-100W.
PRODUCT TYPE	LED STREET LIGHT
POWER OR VOLTAGE REQUIREMENT	100 – 277 VAC
WATTAGE	100 WATTS
FREQUENCY	47 - 60HZ
POWER FACTOR	> 0.95
CCT	5000 K
Ra	> 70
LED LIFETIME	50,000 HRS
LUMEN EFFICIENCY	> 130 LM / W
LUMEN FLUX	> 13000 LM
BEAM ANGLE	TYPE II – M
SURGE PROTECTOR	10 KV
MATERIAL OF THE LAMP	ALUMINUM
MATERIAL OF THE GLASS	TEMPERED GLASS WITH LED
POLE ADAPTER SIZE	D 60 mm
DIMMING TYPE	PHOTOCELL
IP RATING	IP 66
IK RATING	IK 08
OPERATING TEMPERATURE	-40° +50° C
MANUFACTURE WARRANTY	5 YEARS
NET WEIGHT	7.1 KG

ADVANTAGES:

- TOOL FREE OPENING DRIVER CABINET COVER.
- IP66 HIGH WATER PROOF PROTECTION.
- INDIVIDUAL ADJUSTABLE POLE ADAPTER FOR VERTICAL AND HORIZONTAL INSTALLATION.
- LED STREET LIGHT IS ELEGANT AND FASHIONABLE.

QUALITY:

- THIS PRODUCT IS OF HIGH QUALITY AND IT DOES NOT REQUIRE PREVENTIVE MAINTENANCE AFTER PROPER INSTALLATION.
- RESISTANT TO CORROSION, STRONG STORMS, AND MODERATE IMPACTS DUES TO ITS IK 08 RESISTANCE.

NOTE:

- REMOTE / WIRELESS CONTROL SYSTEM AVAILABLE BASE ON PROJECT REQUIREMENTS.
- TECHNICAL SUPPORT 24 HRS, 365 DAYS A YEAR.

**Sictteco Lighting Corp. 10939 Timber Oak Dr. Houston TX 77043
Ph: 713 - 467 - 4778, Cell: 713-382-9906
WWW.SICTTECOLIGHTING.COM**

