SICTTECO LED STREET LIGTH
TYPE SSL-2-100W
SPECIFICATIONS



MODEL	SSL-2-100W.
PRODUCT TYPE	LED STREET LIGHT
POWER OR VOLGATGE REQUIREMENT	100 – 277 VAC
WATTAGE	100 WATTS
FREQUENCY	50 - 60HZ
POWER FACTOR	> 0.95
COLOR TEMPERTURE (CCT)	2700K/3000K/4000K5000 K/6500K
COLOR RENDERING INDEX (IRC)	> 70
LED LIFETIME	50,000 HRS
LUMEN EFFICIENCY	120Lm/w for 2700K/3000K 130Lm/w for 4000K/5000K/6500K
TOTAL LUMEN FLUX	12000 Lm/w for 2700K/3000K 13000Lm for 4000K/5000K/6500K
LIGHT DISTRIBUTION	TYPE II/III/IV/V
SURGE PROTECTOR	10 KV
MATERIAL AND COLOR OF THE LAMP	ALUMINUM LIGHT GREY
MATERIAL OF THE GLASS	TEMPERED GLASS WITH LED
POLE ADAPTER SIZE	D 60 mm
CONTROL TYPE	PHOTOCELL
IP RATING	IP 66
IK RATING	IK 08
OPERATING TEMPERTURE	-40° +50° C
MANUFACTURE WARRANTY	5 YEARS
NET WEIGHT	5.1KG
PACKAGE SIZE	28” X 12” X 7”

ADVANTAGES:

- TOOL FREE OPENING DRIVER CABINET COVER.
- IP66 HIGH WATERPROOF PROTECTION.
- INDIVIDUAL AJUSTABLE POLE ADAPTER FOR VERTICAL AND HORIZONTAL INSTALLATION.
- LED STREET LIGHT IS ELEGANT AND FASHIONABLE.

QUALITY:

- THIS PRODUCT IS OF HIGH QUALITY AND IT DOES NOT REQUIRE PREVENTIVE MAINTENANCE AFTER PROPER INSTALLATION.
- RESISTANT TO CORROSION, STRONG STORMS, AND MODERATE IMPACTS DUES TO ITS IK 08 RESISTANCE.

NOTE:

- REMOTE / WIRELESS CONTROL SYSTEM AVAILABLE BASE ON PROJECT REQUIREMENTS.
- TECHNICAL SUPPORT 24 HRS, 365 DAYS A YEAR.

Sictteco Lighting Corp. 10939 Timber Oak Dr. Houston TX 77043
Ph: 713 - 467 – 4778, Cell: 713-382-9906
WWW.SICTTECOLIGHTING.COM