



SICTTECO LED STREET LIGTH TYPE SSS - LED L-1-30W SPECIFICATIONS

MODEL	SSS – LED L-1-30W.
PRODUCT TYPE	SOLAR LED STREET LIGHT
LUMEN	4000 LM
LED QUANTITY	60 PCS
COLOR TEMPERTURE	6000 – 7000 K (DAY LIGHT)
BEAM ANGLE	150°
LED LIFETIME	50000 HRS
CHARGING TIME	6 – 7 HRS
LIGHT WORKING TIME	12 HRS / NIGHT (DAILY)
LIGHT WORKING RAINY DAYS	3 – 5 DAYS CONTINUOUSLY
DISCHARGING DEFREE	-20° - 60° C
CHARGING DEGREE	-5° - 55° C
STORAGE DEGREE	0° - 45° C
WATERPROOF LEVEL	IP 66
SUITABLE HEIGHT	4 – 6 MTS
INSTALL SPACE	30 – 32 MTS
POLE DIAMETER	60 – 76 mm
LAMP MATERIAL	ALUMINUM ALOY
MANUFATURE WARRANTY	3 YEARS
Ra	> 80
LUMEN EFFICIENCY	> 210 LM / W
NET WEIGHT	6.9 KG

ADVANTAGES:

- HIGH QUALITY BATTERY.
- LONG RAINY LASTING 3 TO 5 DAYS.
- LIGHT CONTROLLED BY REMOTE CONTROL FOR EASY OPERATION.

QUALITY:

- THIS PRODUCT IS OF HIGH QUALITY AND IT DOES NOT REQUIRE PREVENTIVE. MAINTENANCE AFTER PROPER INSTALLATION.
- RESISTANT TO CORROSION, STRONG STORMS, AND MODERATE IMPACTS.

NOTE:

- TECHNICAL SUPPORT 24 HRS, 365 DAYS A YEAR.
- LIGHT CAN BE USE IN GARDENS, PARKS, STREET, PATHWAY, SIDEWALK, PARKING LOTS,